

MODEL	ENGINE TYPE	POWER OUTPUT		ENGINE DATA					OPEN TYPE					SILENT TYPE				
		KVA	KW	NO. OF CYLINDER	BORE x STROKE (mm)	PISTON DISPLACEMENT (liter)	FUEL CONSUMPTION 100% (L/Hr)	OIL CAPACITY (liter)	DIMENSION (mm)			WEIGHT (Kg)	FUEL TANK CAPACITY (liter)	DIMENSION (mm)			WEIGHT (Kg)	FUEL TANK CAPACITY (liter)
									L	W	H			L	W	H		
DG10PE	403D-11G	10	8	3	77 x 81	1.131	2.6	4.9	1200	760	982	307	44	1517	823	1102	430	44
DG14PE	403D-15G	14	11.2	3	84 x 90	1.495	3.6	6.0	1200	760	982	317	44	1517	823	1102	495	44
DG22PE	404D-22G	22	17.6	4	84 x 100	2.216	5.3	6.0	1500	900	1172	655	95	1938	958	1215	885	95
DG33PE	1103A-33G	33	26.4	3	105 x 127	3.300	7.1	7.9	1730	900	1185	750	82	2255	958	1275	950	82
DG50PE	1103A-33TG1	50	40	3	105 x 127	3.300	10.7	7.9	1730	900	1185	800	82	2255	958	1275	1000	82
DG56PE	1103A-33TG2	56	52.8	3	105 x 127	3.300	13.9	7.9	1730	900	1185	830	82	2255	958	1275	1020	82
DG72PE	1104A-44TG1	72	57.6	4	105 x 127	4.400	14.8	8.0	1860	900	1285	970	154	2491	958	1552	1350	154
DG88PE	1104A-44TG2	88	70.4	4	105 x 127	4.400	18.7	8.0	1860	900	1285	1042	154	2491	958	1552	1280	154
DG110PE	1006TG2A	110	88	6	100 x 127	6.000	21.8	16.2	2150	1000	1519	1080	195	3121	1068	1716	1500	195
DG110PE	1104C-44TAG2	110	88	4	105 x 127	4.410	22.6	8.0	1860	900	1315	1050	154	3121	1068	1716	1282	154
DG150PE	1006TAG	150	120	6	100 x 127	6.000	31.5	19.0	2295	1000	1460	1420	195	3321	1068	1732	1800	195
DG155PE	1006TAG2	155	132	6	100 x 127	6.000	41.0	19.0	2295	1000	1460	1440	195	3321	1068	1732	1850	195
DG200PE	1106C-E66TAG4	200	160	6	105 x 127	6.600	40.2	N/A	2300	1100	1643	1920	350	3259	1168	1870	2280	350
DG220PE	1306C-E87TAG3	220	176	6	116.6 x 135.9	8.700	45.2	26.4	2600	1250	1785	1850	473	365	1313	2035	2500	473
DG275PE	1306C-E87TAG6	275	220	6	116.6 x 135.9	8.700	45.0	26.4	2600	1250	1785	1950	473	365	1313	2035	2600	473
DG330PE	2206C-E13TAG2	330	264	6	130 x 157	12.500	76.0	40.0	3100	1400	2004	3217	525	4500	1463	2165	3947	525
DG385PE	2206C-E13TAG2	385	308	6	130 x 157	12.500	75.0	40.0	3100	1400	2004	3292	525	4500	1463	2165	4022	525
DG440PE	2206C-E13TAG3	440	352	6	130 x 157	12.500	85.0	40.0	3190	1400	2004	3427	525	4500	1463	2165	4157	525
DG500PE	2506C-E15TAG1	500	400	6	137 x 171	15.200	95.0	62.0	3430	1420	2187	3900	870	5022	1652	2475	4895	870
DG550PE	2506C-E15TAG2	550	440	6	137 x 171	15.200	106.0	62.0	3430	1420	2187	3985	870	5022	1652	2475	4980	870
DG550PE	2806A-E18TAG1A	550	528	6	145 x 183	18.100	123.0	62.0	3450	1535	2151	4600	1200	5022	1652	2475	5500	1200
DG715PE	2806A-E18TAG2	715	572	6	145 x 183	18.100	127.0	62.0	3581	1698	2186	4750	1200	5022	1652	2475	5750	1200
DG800PE	4006-23TAG2A	800	640	6	160 x 190	22.900	177.0	113.4	4000	1800	2300	5100	500	6058	2438	2591	9750	500
DG800PE	4006-23TAG3A	800	720	6	160 x 190	22.921	200.0	113.4	4000	1800	2300	5240	500	6058	2438	2591	9750	500
DG1100PE	4008TAG2A	1100	880	8	160 x 190	30.561	220.0	165.6	4665	2050	2300	7900	500	6058	2438	2591	12900	500
DG1400PE	4012-46TVG2A	1400	1120	12	160 x 190	45.842	259.0	177.0	4752	1858	2344	N/A	N/A	N/A	N/A	N/A	N/A	N/A
DG1550PE	4012-46TAG2A	1550	1320	12	160 x 190	45.842	301.0	177.0	5200	2200	2410	10000	N/A	N/A	N/A	N/A	N/A	N/A
DG1875PE	4012-46TAG3A	1875	1500	12	160 x 190	45.842	283.0	177.0	5200	2200	2410	11050	N/A	N/A	N/A	N/A	N/A	N/A
DG2250PE	4016TAG2A	2250	1800	16	160 x 190	61.123	209.0	237.2	5800	2250	2900	12000	N/A	N/A	N/A	N/A	N/A	N/A
DG2420PE	4016-61TRG3A	2420	1936	16	160 x 190	61.123	N/A	237.2	5800	2250	2900	12214	N/A	N/A	N/A	N/A	N/A	N/A

* POWERZONE reserve the rights to modify model and technical specifications without prior notification.



MODEL	ENGINE TYPE	POWER OUTPUT		ENGINE DATA					OPEN TYPE				SILENT TYPE					
		KVA	KW	NO. OF CYLINDER	BORE x STROKE (mm)	PISTON DISPLACEMENT (liter)	FUEL CONSUMPTION 100% (L/Hr)	OIL CAPACITY (liter)	DIMENSION (mm)			WEIGHT (Kg)	FUEL TANK CAPACITY (liter)	DIMENSION (mm)			WEIGHT (Kg)	FUEL TANK CAPACITY (liter)
									L	W	H			L	W	H		
DG30CE	4BT3.9-G2	30	24	4	102 x 120	3.92	6.5	6.0	1860	900	1360	820	154	2490	955	1552	1200	154
DG43CE	4BT3.9-G2	43	34.4	4	102 x 120	3.92	9	6.0	1860	900	1360	850	154	2490	955	1552	1240	154
DG56CE	4BTA3.9-G2	56	52.8	4	102 x 120	3.92	13	7.9	1860	900	1381	950	154	2491	955	155	1280	154
DG110CE	6BT5.9-G2	110	88	6	102 x 120	5.90	23	14.2	2150	1000	1469	1280	195	3121	1068	1716	1700	195
DG175CE	6CTA8.3-G2	175	140	6	114 x 135	8.30	35	19.0	2300	1100	1681	1780	350	3259	1168	1866	2200	350
DG200CE	6CTA8.3-G2	200	160	6	114 x 135	8.30	40	18.9	2335	1100	1681	1860	350	3259	1168	1855	2280	350
DG220CE	6CTA8.3-G2	220	176	6	114 x 135	8.30	44	26.4	2600	1250	1684	1910	473	3650	1313	2035	2330	473
DG275CE	6LTA8.9-G2	275	220	6	114 x 145	8.90	52	26.5	2600	1250	1684	2050	473	3650	1313	2035	2600	473
DG330CE	NTA855-G1A	330	264	6	140 x 152	14.00	65	40.0	3031	1150	1978	2336	526	4500	1463	2165	3800	526
DG350CE	NTA855-G1B	350	280	6	140 x 152	14.00	70	40.0	3031	1400	1978	3120	526	4500	1463	2165	3850	526
DG385CE	NTA855-G2A	385	308	6	140 x 152	14.00	77	60.6	3031	1400	1978	3250	526	4515	1463	2165	3920	526
DG550CE	KTA19-G4	550	440	6	159 x 159	18.90	104	50.0	3400	1580	2055	4200	500	5022	1652	2475	5345	893
DG550CE	QSK15-G8	550	440	6	137 x 169	15.00	103	91.0	3550	1355	2050	3950	870	5022	1652	2475	5090	893
DG680CE	KTA19-G6A	680	544	6	159 x 159	18.90	128	65.0	3645	1595	2095	4870	740	5200	1850	2450	5960	890
DG825CE	KTA38-G2	825	650	8	159 x 159	37.80	157	135.0	4370	2050	2397	6250	900	5800	2260	2550	8250	500
DG1000CE	KTA38-G2A	1000	800	12	159 x 159	37.80	191	135.0	4370	2050	2397	7950	900	5800	2260	2550	12750	500
DG1100CE	KTA38-G5	1100	880	12	159 x 159	37.80	209	135.0	4370	2050	2397	9500	1000	5800	2271	2550	12750	500
DG1375CE	KTA50-G3	1375	1100	16	159 x 159	50.30	251	177.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
DG1410CE	KTA50-G3	1410	1128	16	159 x 159	50.30	251	177.0	4900	1780	2380	9400	N/A	N/A	N/A	N/A	N/A	N/A
DG1675CE	KTA50-G5B	1675	1340	16	159 x 159	50.30	309	204.0	5570	2100	2538	10570	N/A	N/A	N/A	N/A	N/A	N/A

* POWERZONE reserve the rights to modify model and technical specifications without prior notification.